FACTORIZED TOPIC MODELS

Cheng Zhang, Carl Henrik Ek, Andreas Damianou, Hedvig Kjellström

{chengz, chek, hedvig}@kth.se, andreas.damianou@sheffield.ac.uk





The University Sheffield.

ABSTRACT

We present a modification to a latent topic model, which makes the model exploit supervision to produce a factorized representation of the observed data. The structured parameterization separately encodes variance that is shared between classes from variance that is private to each class by the introduction of a new prior over the topic space. The approach allows for a more efficient inference and provides an intuitive interpretation of the data in terms of an informative signal together with structured noise. The factorized representation is shown to enhance inference performance for image, text, and video classification.

MOTIVATION




Illustration of topic distribution θ and θ^{class} . K=10 is used here as an example


ACKNOWLEDGEMENT

This research has been supported by the EU through TOMSY, IST-FP7- Collaborative Project-270436, and the Swedish Research Council (VR).

REFERENCES

- [1] D. M. Blei, A. Y. Ng, and M. I. Jordan. Latent Dirichlet Allocation Journal of Machine Learning Research, 3:993-1022, 2003
- [2] L. Fei-Fei and P. Perona. A Bayesian hierarchical model for learning natural scene categories In CVPR, 2005.
- [3] D. M. Blei and J. D. McAuliffe. Supervised topic models In NIPS, 2007

Model



Our factorized LDA

We employ an entropy-like measure H(k) over class for each topic k:

$$H(k) = \frac{1}{\log(1/C)} \sum_{c=1}^{C} \frac{\theta_{c,k}^{\text{class}}}{\sum_{\xi=1}^{C} \theta_{\xi,k}^{\text{class}}} \log(\frac{\theta_{c,k}^{\text{class}}}{\sum_{\xi=1}^{C} \theta_{\xi,k}^{\text{class}}})$$
• High $H(k) \to \text{class-independent topics}$

- Low $H(k) \to \text{class-depended topics}$

Hence we introduce the following function:

$$A(k) = H(k)^2 - H(k) + 1$$

We define the new prior as:


0.5 0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1

The static function A

$$p(\boldsymbol{\theta}) \propto \prod_{k=1}^{K} A(k)$$
,

which treats each column of θ^{class} independently. With the additional prior, the generative model becomes:

$$p(\mathbf{w}|\alpha, \pi, c) = \int p(\boldsymbol{\theta}|\alpha, c) p(\boldsymbol{\theta}) \left(\prod_{n=1}^{N} \left[\sum_{z_n} p(z_n|\boldsymbol{\theta}) p(w_n|z_n, \boldsymbol{\beta}) \right] p(\boldsymbol{\beta}|\pi) \right) d\boldsymbol{\theta} .$$



optimization function A

We introduce an "auto-annealing" procedure, where Ais changed to dynamic function, since H is close to 1 during initialization.

$$A(k) = H(k)^2 - 2\hat{H}H(k) + 1 , \qquad (1)$$

where the average H, $\hat{H} = \sum_{k=1}^{K} H(k)/K$, is used as an annealing parameter in the function.

We consider topics with low H as class-dependent while topics with high H are considered as independent.

An additional factor \mathcal{F}_{ck} is introducted in the update equation of the Gibbs Sampling,

$$p(z_i = k | \vec{z}_{\neg i}, \vec{w}, \alpha, \pi, \kappa) \propto \frac{n_{k, \neg i}^{(t)} + \pi_t}{\sum_{t=1}^{V} n_{k, \neg i}^{(t)} + \pi_t} \cdot \frac{n_{m, \neg i}^{(k)} + \alpha_k}{\left[\sum_{k=1}^{K} n_m^{(k)} + \alpha_k\right] - 1} \cdot \mathcal{F}_{ck}.$$

In the updating procedure for \mathcal{F}_{ck} a gradient step is carried out by measuring the possible change with respect to the prior $\Delta A(k) = A^{\text{assume}}(k) - A(k)$, where $A^{\text{assume}}(k)$ is the evaluation of Eq. 1 for the current sample. $\Delta A(k) \in (-1,1)$. Thus the factor takes the following form,

$$\mathcal{F}_k = 1 + \Delta A(k)$$
.


We introduce a parameter κ that controls the contribution of this term, hence

$$\begin{cases} \mathcal{F}_k = 1 + |\Delta A(k)|^{\kappa}, & if \ \Delta A(k) > 0 \\ \mathcal{F}_k = 1 - |\Delta A(k)|^{\kappa}, & if \ \Delta A(k) < 0. \end{cases}$$


EXPERIMENTS

We evaluated our model(F-LDA) against regular LDA model [2] and SLDA [3] on four different classification tasks with different data.

• Object Classification





The toy dataset used in the object classification




• Text Classification

regular LDA: 34.38%






SLDA: 0%




F-LDA: 81.25%

• Scene Classification



 $heta^{
m class}$ with F-LDA

• Action Classification



1 2 3 4 5 6 7 8 9 10

 $\boldsymbol{\theta}^{\mathrm{class}}$ with SLDA

 $heta^{
m class}$ with F-LDA

1 2 3 4 5 6 7 8 9 10

CIDA

Performance	Regular LDA	SLDA	LDA
Text Classification	74.63%	63.75%	83.91%
Scene Classification	80.50%	84.00%	84.50%
Action Classification	38%	52.33%	65.22%